HAND DRYERS




ML_1800_WHT

Automatic Operation ABS Hand Dryer

Specification

| Casing | 3.0mm White High Grade Fire Retardent ABS |
|---------------|--|
| Motor | 80W Brushless, 2850 RPM 105°C auto reset overload |
| Power Use | 240V, 50Hz, 1800W, 7.50A |
| Sound Level | 55db (+/- 3) |
| Drying time | 30-35 seconds |
| DP Rating | IPX 1 |
| Heater | 87°C auto resetting thermostat 141°C auto reset safety cut off |
| Warm Air | Speed: 14.5m/s |
| | Temp: Ambient +20°C |
| Protection | 60 sec power cut off, auto reset |
| Timing | 2 sec delay turn off after last read |
| Sensor/Range | Auto Infrared - 180mm +/-20mm preset, 100 - 300mm adjust |
| Case Security | 2 SS theft resistant hex drive screws (hex key supplied) |
| Net Weight | 3.5kg |
| Dimensions | 259.99W x 216.99H x 179.99D |
| Warranty | 5 Year Warranty (3 Years Parts and Labour + 2 Years Parts only) |
| Note | Unit can be hard wired by electrician or used with cord and plug provided * This unit is accessible compliant when installed in accordance with AS1428.1. guidelines. |





Downloads & Resources

Care & Maintenance Mounting template Revit Promotions

The photographs and line drawings of the products presented above are representational only. Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.