HAND DRYERS




ML_ECOSLENDER05_SS

EcoSlender Slimline Automatic Operation Hand Dryer

Specification

•			
Material	1.2mm #304 Satin Stainless Steel		
Features	Contemporary curved design Patented high-flow dual air outlets		
Motor	Brush Type Dual Ball Bearings 16,000-29,000 RPM 95°C auto reset overload		
Power Use	240V, 50Hz, 1000W, 4.17A		
Sound Level	68.9dB - 74.3dB (Adjustable)		
Drying time	Less than 15 seconds		
DP Rating	IP 24		
Element	325W - 500W (Adjustable)		
Heater	ON/OFF Heating Options 85°C auto resetting thermostat 142°C auto reset safety cut off		
Warm Air	Speed: 45.5m/s - 70m/s (Adjustable)		
	Temp: Ambient +25°C		
Protection	60 sec power cut off, auto reset		
Sensor/Range	Infrared Automatic, Self Adjusting 170mm+/-20mm Blue LED indicates operation/range		
Case Security	2 SS theft resistant hex drive screws (hex key supplied)		
Net Weight	3.8kg		
Dimensions	275.5mmW x 216mmH x 100mmD		
Warranty	5 Year Warranty (3 Years Parts and Labour + 2 Years Parts only)		
Note	Unit can be hard wired by electrician or used with cord an plug provided		
	* This unit is accessible compliant when installed in accordance with AS1428.1. guidelines.		
Related Video	Stainless Steel Cleaning & Maintenance		

















Downloads & Resources

Care & Maintenance Mounting template Revit

Promotions