




EcoMo Auto Operation High Speed Hand Dryer

SPECIFICATIONS

Cover/ Specify	3.0mm thick moulded Antibacterial ABS plastic White: ML_ECOMOROUND_WHT Silver: ML_ECOMOROUND_SIL Black: ML_ECOMOROUND_BLK
Motor	350-700 W, 12,000-18,000 R.P.M., Adjustable Brush Motor
Motor Thermal Protection	Auto resetting thermostat turns unit off 240V/277V at 95°C
Power Use	220-240 Vac, 50/60Hz, 6.1-6.7 A, 1.34-.16kW
Standby Power	0.3-0.4W
LED Colour	Standby: Red, Active:Blue
Sound Level	Min 72.2 dB to 75.4 dB MAX at 1m
Drying time	10-15 seconds
Drip Proof	IP 21
Heater Element	ON/OFF switch available. Power 450-900W depending on air speed
Heater Thermal Protection	Auto resetting thermostat turns unit off at 85°C Thermal cut-off at 142°C
Warm Air Speed	75-90 m/s (adjustable)
Air Output	55°C - Ambient Temp. 25°C
Timer Protection	60 seconds auto shut off
Circuit/ Sensor Range	Circuit Operation- Infrared Automatic, self adjusting Sensor Range Standard 170mm ± 20mm Adjustable
Case Security	SS theft resistant hex drive screws (hex key supplied)
Net Weight	9.4kg
Dimensions	322mmW x 624.5mmH x 185mmD
Filter	Super Filter Assembly consisting of Antibacterial Filter+Carbon Filter + HEPA Filter
Warranty	5 Year Warranty (3 Years Parts and Labour + 2 Years Parts only)
Note:	* Unit can be hard wired by electrician or used with cord and plug provided * This unit is disabled compliant when installed in accordance with AS1428.1. guidelines.



The photographs and line drawings of the products presented above are representational only.
Metlam Australia Pty Ltd reserves the right to, and from time to time, make changes and improvements in design and dimensions.